

Linux + IA 2025/05/18

SGPT

- Instalación:

```
pipx install shell-gpt
```

- Configuración:

```
nano ~/.config/shell_gpt/.sgptrc
```

- Parametros a modificar:

- [.sgptrc](#)

```
CHAT_CACHE_PATH=/tmp/chat_cache
CACHE_PATH=/tmp/cache
CHAT_CACHE_LENGTH=100
CACHE_LENGTH=100
REQUEST_TIMEOUT=60
#DEFAULT_MODEL=gpt-5.4-mini
DEFAULT_MODEL=qwen2.5-coder:0.5b
DEFAULT_COLOR=magenta
ROLE_STORAGE_PATH=/home/jared/.config/shell_gpt/roles
DEFAULT_EXECUTE_SHELL_CMD=false
DISABLE_STREAMING=false
CODE_THEME=dracula
OPENAI_FUNCTIONS_PATH=/home/jared/.config/shell_gpt/functions
#OPENAI_USE_FUNCTIONS=true
OPENAI_USE_FUNCTIONS=false
SHOW_FUNCTIONS_OUTPUT=false
#API_BASE_URL=default
API_BASE_URL=http://localhost:11434/v1
PRETTYIFY_MARKDOWN=true
USE_LITELLM=false
SHELL_INTERACTION=true
OS_NAME=auto
SHELL_NAME=auto
#OPENAI_API_KEY=
OPENAI_API_KEY=ollama
```

- Ej:

```
sgpt "Comando para listar procesos"
sgpt --shell "Crea un archivo hola.md con el contenido 'Nota rápida'"
```

From:

<https://dw.openit.dev/> - **DokuWikiOpenIT**

Permanent link:

<https://dw.openit.dev/lia20260518?rev=1779149779>

Last update: **2026/05/19 00:16**

